

AIR DRYER SYSTEM MODEL: HAD-1.5



AIR DRYER SYSTEM 0.6/40-BAR

MODEL HAD-1.5
BRAND NAME "PIONEERAIR"

No.	Item	Technical Parameters	
1	Gas-water separator	1. Rated treatment capacity	: 2 m ³ /min
		2. Rated working pressure	: 4.0 MPa
		3. Air intake temperature	: ≤80°C
		6. Water removal rate (liquid)	: 99%
		5. Oil content	: ≤10ppm
2	Refrigerant Air	1. Rated treatment capacity	: 1.5Nm ³ /min
	working pressure	: 4.0 MPa	dryer 2. Rated
		3. Pressure dew point	: 3-10°C
		4. Refrigeration Power	: 1/2 HP
		5. Air intake temperature	: ≤45°C
		6. Cooling	: Air-cooled

7. Recommended ambient temperature : $\leq 38^{\circ}\text{C}$
8. Supply voltage : AC220V50Hz



P. O. Box No.: 23097, Sharjah, U.A.E | Main Office Tel. No. +971-6-5338277, Fax No. : +971-6 -5332868

Branch Tel No.: +9716-5439350, | E-mail: narex@emirates.net.ae; narexind@eim.ae; www.narexuae.com

CHOOSE WISELY

1 | Page

9. Electronic automatic drain valve to drain off condensate water from the system

- | | | | |
|---|---------------------------|-----------------------------|------------------------|
| 3 | Precision Filter C | 1. Rated treatment capacity | : 2m ³ /min |
| | | 2. Rated working pressure | : 4.0 MPa |
| | | 3. Filtering accuracy | : 1μm |
| | | 4. Residual oil | : 1 ppm |
| 4 | Precision Filter T | 1. Rated treatment capacity | : 2m ³ /min |
| | | 2. Rated working pressure | : 4.0 MPa |
| | | 3. Filtering accuracy | : 0.01μm |
| | | 4. Residual oil | : 0.01 ppm |
| 5 | Precision Filter C | 1. Rated treatment capacity | : 2m ³ /min |
| | | 2. Rated working pressure | : 4.0 MPa |
| | | 3. Filtering accuracy | : 0.01μm |
| | | 4. Residual oil | : 0.003 ppm |

Dimension (L x W x H) : 800x650x950mm

Weight : 95kgs

Brand New : **China**

P. O. Box No.: 23097, Sharjah, U.A.E | Main Office Tel. No. +971-6-5338277, Fax No. : +971-6 -5332868



NAREX INDUSTRIAL MACHINERY L.L.C.

Branch Tel No.: +9716-5439350, | E-mail: narex@emirates.net.ae; narexind@eim.ae; www.narexuae.com

CHOOSE WISELY

2 | Page